

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US2006/013765

International filing date: 13 April 2006 (13.04.2006)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 60/672,834
Filing date: 19 April 2005 (19.04.2005)


Date of receipt at the International Bureau: 06 June 2006 (06.06.2006)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse

1472958



THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

May 30, 2006

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/672,834

FILING DATE: *April 19, 2005*

RELATED PCT APPLICATION NUMBER: PCT/US06/13765

THE COUNTRY CODE AND NUMBER OF YOUR PRIORITY APPLICATION, TO BE USED FOR FILING ABROAD UNDER THE PARIS CONVENTION, IS *US60/672,834*



Certified by

Under Secretary of Commerce
for Intellectual Property
and Director of the United States
Patent and Trademark Office

041905

20427

PTO/SB/16 (12-04)

Approved for use through 07/31/2006. OMB 0651-0032

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET


This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

Express Mail Label No. EV 363553689 US

11:268 U.S. PTO
607672834

041905

INVENTOR(S)		
Given Name (first and middle (if any))	Family Name or Surname	Residence (City and either State or Foreign Country)
Lewis B. J. Casey	Benson Schutz	Sewickley, PA Crescent, PA
Additional inventors are being named on the _____ separately numbered sheets attached hereto		
TITLE OF THE INVENTION (500 characters max):		
METHOD FOR PRODUCING ACTIVATED LIME FOR REMOVAL OF ACID GASES FROM A COMBUSTION GAS		
Direct all correspondence to: CORRESPONDENCE ADDRESS		
<input type="checkbox"/> The address corresponding to Customer Number: 09979		
OR		
<input type="checkbox"/> Firm or Individual Name Address City State Zip Country Telephone Fax		
ENCLOSED APPLICATION PARTS (check all that apply)		
<input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76 <input type="checkbox"/> CD(s), Number of CDs _____		
<input checked="" type="checkbox"/> Specification Number of Pages <u>5</u> <input type="checkbox"/> Other (specify) _____		
<input checked="" type="checkbox"/> Drawing(s) Number of Sheets <u>2</u>		
Application Size Fee: If the specification and drawings exceed 100 sheets of paper, the application size fee due is \$250 (\$125 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(e).		
METHOD OF PAYMENT OF FILING FEES AND APPLICATION SIZE FEE FOR THIS PROVISIONAL APPLICATION FOR PATENT		
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.		TOTAL FEE AMOUNT (\$) <div style="border: 1px solid black; padding: 5px; width: 100px; margin: 0 auto;">200.00</div>
<input checked="" type="checkbox"/> A check or money order is enclosed to cover the filing fee and application size fee (if applicable).		
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached		
<input type="checkbox"/> The Director is hereby authorized to charge the filing fee and application size fee (if applicable) or credit any overpayment to Deposit Account Number: <u>16-0485</u> . A duplicative copy of this form is enclosed for fee processing.		
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.		
<input checked="" type="checkbox"/> No.		
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____		

SIGNATURE 
 TYPED or PRINTED NAME William G. Kratz, Jr.
 TELEPHONE 412-281-2931

Date April 19, 2005
 REGISTRATION NO. 22,631
 (if appropriate)
 Docket Number: 04037

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Docket No.: 04037

CERTIFICATE OF MAILING

Express Mail Label No. EV 363553689 US

I hereby certify that, on April 19, 2005, the attached Provisional Patent Application and Assignment were deposited with the United States Postal Service as Express Mail utilizing the Express Mail Post Office to Addressee Service, postage pre-paid, addressed to:

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Barbara A. Konopski
(Signature)

Barbara A. Konopski

April 19, 2005

METHOD FOR PRODUCING ACTIVATED LIME FOR REMOVAL OF ACID GASES FROM A COMBUSTION GAS

BACKGROUND OF THE INVENTION

The present invention relates to a method of producing an activated calcium oxide for use in the removal of acid gases, such as sulfur trioxide vapor, sulfur dioxide, hydrogen chloride and hydrogen fluoride from combustion gases, such as those produced in industrial plants.

Hydrated lime (calcium hydroxide) has been used for capture of sulfuric acid or sulfur trioxide vapor. For sulfur trioxide control, hydrated lime has been injected into flue gas in a coal-fired power plant ahead of a particulate collector, usually an electrostatic precipitator (ESP). Flue gas temperature at this location is 300-350°F. Capture of SO_3 is marginally effective with normal hydrated limes. The specific surface area of normal hydrated lime ranges from 10-23 square meters per gram, and the specific surface area is unchanged upon injection at this temperature range. Specially prepared hydrated limes with higher than normal specific surface areas ranging from 25-38 square meters per gram are more effective at capturing sulfur trioxide via injection ahead of an ESP. Specially prepared hydrated limes include thus prepared with additives (glycols, amines, and alcohols) and those prepared with excess water. The disadvantages of these specially prepared hydrated limes include cost of additives and cost from drying excess water from the product. Also, additives may contaminate other hydrated lime products produced in the same hydration plant and make these other products unsuitable. Although a number of patents on specially prepared hydrated limes claim substantially improved specific surface areas, none of these products are produced commercially in the United States due to the noted disadvantages.

Although it is already well-known that thermal decomposition of calcium hydroxide (to calcium oxide and water vapor) increases its reactivity with sulfur dioxide, it is not well-known that thermal decomposition may also increase reactivity with sulfur trioxide. Also, although it is well-known that calcium hydroxide decomposes near 1076°F, it is not well-known that decomposition can begin at as low as 750°F. Test data shows that partial decomposition at 750°F yields a large increase in the number of active sites available for acid gas absorption. Moreover, test data shows that decomposition at the well-known temperature of 1076°F yields fewer active sites than decomposition at 750°F.

One aspect of the invention is that calcium hydroxide is prepared from hydrated lime and is activated for acid gas capture at a much lower temperature than the well-known decomposition temperature of 1076°F for calcium hydroxide (reference, CRC Handbook of Chemistry and Physics, 53 ed., p. B-77).

SUMMARY OF THE INVENTION

An activated lime for use in the removal of acid gases from a combustion gas stream is prepared by thermally decomposing calcium hydroxide to produce calcium oxide by contacting the calcium hydroxide with a heated gaseous stream having a temperature of between 750-950°F, such that calcium oxide is produced that has a specific surface area of between about 36-42 square meters per gram, and collecting the resultant calcium oxide so produced for use later in contact with a combustion gas stream to remove acid gases therefrom.

DETAILED DESCRIPTION OF THE INVENTION

An activated lime is produced according to the present method for use in removing acid gases from a combustion gas stream. Examples of acid gases in a combustion gas stream include sulfur trioxide, sulfur dioxide, hydrogen chloride, hydrogen fluoride, and the like.

In the present method, the calcium hydroxide (hydrated lime) is contacted with a hot gas stream at a temperature of between 750-950°F, which gas stream may comprise a combustion gas stream or air.

The calcium hydroxide may be activated at any source thereof, for example, from hydration of lime at a lime production facility, and collected and then shipped for use at a site for removal of acid gases from a combustion gas stream.

Fig. 1 illustrates an embodiment where a combustion gas stream from combustor 1 is at a temperature below about 750°F. The combustion gas stream flows through line 2 to a contactor 3. At least a portion of the combustion gas stream is diverted through line 4 to a heater 5 where the combustion gas stream is heated to a temperature between 750-950°F and then passed through line 6. Calcium hydroxide from a source 7 is charged through line 8 to the line 6 for contact with the heated combustion gas stream. The calcium hydroxide is thermally decomposed to provide an activated lime having a specific surface area of between about 36-42 square meters per gram and is collected in collector 9. The activated lime is charged from collector 9 through line 10 to the contactor 3 where it reacts with and removes acid gases from the combustion gas stream fed through line 2. The contactor 3 may be a separate unit into which the line 2 feeds or may be a portion of the contactor line 2. After contact, the clean gas stream is passed

passed through line 11 to a separator 12, such as an electrostatic precipitator, and solids are removed therefrom through line 13, while the combustion gas stream, with acid gases removed therefrom, is discharged through line 14.

In the embodiment illustrated in Fig. 2, hot air is used to heat and decompose the calcium hydroxide. As illustrated, a combustion gas stream from combustor 15, at a temperature below about 750°F flows through line 16 to a contactor 17. Hot air, at a temperature of between 750-950°F, from a source 18, is passed through line 19. Calcium hydroxide from a source 20 is charged through line 21 to the line 19 for contact with the heated air stream. The calcium hydroxide is thermally decomposed to provide an activated lime having a specific surface area of between 36-42 square meters per gram and is collected in collector 22. The activated lime is charged from collector 22 through line 23 to the contactor 17 where it reacts with acid gases from the combustion gas stream fed through line 16. After contact, the clean gas stream is passed through line 24 to a separator 25, such as an electrostatic precipitator, and solids are removed therefrom through line 26, while the combustion gas stream, with acid gases removed therefrom, is discharged through line 27.

Fig. 3 shows the number of active absorption sites (as specific surface area, square meters per gram) vs. temperature for thermal decomposition in air of three different hydrated limes. The data clearly shows that the specific surface area increases sharply at about 750°F and declines rapidly at temperatures above about 950°F.

What is Claimed is:

1. A method of forming an activated lime for the removal of acid gases from a combustion gas stream comprising;

thermally decomposing calcium hydroxide to produce calcium oxide by contacting the calcium hydroxide with a gaseous stream having a temperature of between 750–950°F whereby calcium oxide is produced having a specific surface area of between about 36 – 42 square meters per gram; and

collecting the calcium oxide so produced for use in contact with a combustion gas stream to remove acid gases therefrom.

2. The method of forming an activated lime for removal of acid gases from a combustion gas stream as defined in Claim 1 wherein said temperature is between about 750-850°F.

3. The method of forming an activated lime for removal of acid gases from a combustion gas stream as defined in Claim 1 wherein said gaseous stream is a combustion gas stream.

4. The method of forming an activated lime for removal of acid gases from a combustion gas stream as defined in Claim 1 wherein said gaseous stream is air.




FIG. 1




FIG. 2




FIG. 3